

Costrite Garage

- Built to protect your car or boat from the wildest weather conditions
- Tailored to fit anything from a mini through to a people mover

SPECIFICATIONS	COSTRITE Garage	
Roof	Pitched at 11° Hi Tensile BLUESCOPE® roof sheeting 0.47mm thick (TCT)	
Heights	Any height up to 3.0 metres	
Widths	Any width up to 8.0 metres	
Windows	600 x 900m to 900 x 1800m	
Garage Doors	Roller Doors x 2	B&D® or Gliderol®, keyed alike Standard width 2460mm wide gable end or side wall fitted
	Personal Door x 1	820mm x 2000mm RHS galvanised fully welded frame
Wall Sheeting	Hi Tensile BLUESCOPE® wall sheeting 0.40mm thick (TCT) Multiclad® profile in either Zinalume® or Colorbond® finish	
Guttering Barge Caps & Downpipes	Quad guttering in Zinalume® or Colorbond® supplied by BLUESCOPE® steel	
Fixings	Neoprene washers on all roof tek screws for better water protection. Wall teks colour coded to match the shed	
Portal Frame	Galvanised high tensile steel. Middle portal are made from 150mm "C" section Bolted bracket system at the knee and apex connections	
Slab	Standard 100mm thick, 25 MPA concrete, F62 mesh with footings under all portals. Rebated slab for waterproofing of roller doors. Industrial slabs can be designed for heavier use	
Connections	3mm thick nickel plated bracket at the apex and knee joint with 12mm bolts. 6mm base plate bracket.	
Anchorage	16mm dynabolts® into slab.	
Roof purlins and wall girts	Purlins and girts are full length up to 8 metres and then, if joined, overlap a minimum of 400mm	
Bracing	Wind bracing is 30 x 1.0mm galvanised strap all screwed with class 3 teks	
Special Features	Tailored to suit your requirement Full range of accessories	

Disclaimer – Please be aware that our specifications and product range are subject to change without notice.



Adro Garages and Carports Pty Ltd
(Head Office & Display Centre)
Ph: (07) 3875 1452
Fax: (07) 3274 2535
31 Meadow Avenue, Coopers Plains Qld 4108
ABN 97 082 008 688 31

*Custom built designs to cover your needs...
any size, any shape, any place!*

www.adro.com.au