

# Solarspan® Patio

ADRO's professional and industry experience in building patios over the years has given us the skills and experience to tailor Solarspan® patios to suit your requirements.

# Flatdek® Patio

Flatdek® patios have a span capability of 3.5 metres, and include an attractive ceiling or internal finish.

The Flatdek® has a unique profile and an excellent structural performance. The overlapping cladding provides clean lines from the underside of the patio.

SPECIFICATIONS	SOLARSPAN® AND FLATDEK® PATIOS
Roof	The Solarspan® insulated roof panel is a sandwich panel with hi tensile steel sheeting on both sides. The Flatdek® profile is hi-tensile BLUESCOPE® steel sheeting
Heights	Up to 3.0 metres high
Widths	Solarspan® - Up to 5.0 metres span Flatdek® - Up to 3.5 metres span
Guttering Barge Caps & Downpipes	Zincalume® or Colorbond® supplied by BLUESCOPE® steel
Fixings	Can be attached to existing metal house fascia using receiving channel.
Frame	Fully powdercoated prefabricated system Columns are 65mm x 65mm RHS powdercoated to match colour choices
Slab	Can be dyna bolted to a slab or posts set into footings into the ground. If a slab is chosen, the slab dimension is 100mm wider and longer than the roof dimension
Connection Plates	All powdercoated to match colour choices
Anchorage	12mm dyna bolts when fixing to a slab or posts cast into concrete footing if not

Disclaimer – Please be aware that our specifications and product range are subject to change without notice.



**Adro Garages and Carports Pty Ltd**  
(Head Office & Display Centre)  
Ph: (07) 3875 1452  
Fax: (07) 3274 2535  
31 Meadow Avenue, Coopers Plains Qld 4108  
ABN 97 062 008 688 31

*Custom built designs to cover your needs...  
any size, any shape, any place!*

[www.adro.com.au](http://www.adro.com.au)